





Cym Materiales SA manufactures continuous flow equipment for shot blasting welded structural shapes, profiles, bars, plates, steel strips and pipes according to the needs of each customer.

The **abrasive** is propelled by centrifugal turbines. The number of turbines for each machine depends on the size of the parts to be blasted or the speed required.

In the **PER** and **CH** equipment lines, the blast wheels are located at 90 degrees from the parts pass-line, while in the **PER-I** and **EST** line, they are located at different abrasive projection angles.

The conveyors may be a parallel roller bed or an overhead rail conveyor that introduces the parts into the chamber continuously. The machine may be equipped with in-line painting to avoid costly secondary handling of the parts.

Features Construction



Maintenance Platform

- to access to the top elevator and air wash abrasive separator

Air Wash Abrasive Separator

- Used abrasive and fines are stored behind a fixed, but adjustable metering gate. Abrasive and fines are allowed to fall in a uniform curtain through the airwash separation zone.



Intermediate **Gravitational Separator**

- Increasing the air flow inside the cabinet without risk of carry good abrasive to the dust collector.



Bi-directional Blast Wheel

- Located strategically with a correct distribution of the shot on the parts to be treated resulting in a better coverage and better performance of the machine
- Power ranging from 7.5 HP a 50 HP
- Direct drive or Belt drive according to customer request





Dust Collector

- Maximum dust emission < 1 mgr/m3
 - Easy replacement of cartridges
 - Continuous cleaning system



Roller Conveyor

- Robust and modular manufacturing for different ranges of lengths and weights - Working speed Frequency-
- controlled gear motor - Screw conveyor to return
- abrasives that can go along with the piece to the machine



Control Panel

- According to IEC, Nema, UE
- Automatic PLC Control



Blast Cabinet

- Inlet and outlet chambers with sealing curtains to minimize abrasive escape from the blast compartment
- Wide maintenance door for expedited and hassle free maintenance cabinet and curtains.
- Two layers of lining made of
 - Manganese Steel cover the totality of the cabinet
 - · Second lining with high chrome in hot area



Technical Data - Steel Construction Shotblasting System - EST

										•
Model		Blast Wheel		Section mm (*)		Material				Working Speed
		Qty.	Нр	Width	High	Profile	Struct ures	Plates	Pipes Spool	Mts. / min (**)
	EST 6 x 15	8	7.5/15/ 30	600	1500	X	X	X	X	0.4 a 6
	EST 15 X 10	8	7.5/15/ 30	1500	1000	X	X	X	X	0.3 a 5
	EST 15 X 15	8	7.5/15/ 30	1500	1500	X	X	X	X	0.3 a 4
	EST 15 X 20	12	10/20/30	1500	2000	X	X	X	X	0.4 a 5
	EST 15 x 25	12	10/20/30	1500	2500	X	X	X	X	0.3 a 4.5
	EST 25 X 15	16	15/20/30	2500	1500	X	X	X	X	0.4 a 6
	EST 25 X 25	16	15/20/30	2500	2500	X	Χ	X	X	0.3 a 5

Note:

- (*)The maximum parts pass size section and the production speed can be adapted to the customer precise requirement.
- (**)The production can vary depending the degree of rust, mill scale, and or other contaminants present
- (***)If the equipment you require is not in this catalog please contact our sales or engineering departments which will help to develop the best equipment to suit your needs with our goal to reduce operating costs and increase profitability in your production systems.





Advantages of wheel blast machines:

- Alto volumen de producción, con mínimo costo operativo.
- Higher production volume, minimizing operating cost.
- Enhanced finish consistency of processed pieces.
- Automatic shot blasting process, which does not require skilled labor.
- With proper equipment operation, there are no health problems for the staff, or damage to the facilities.
- They do not pollute the environment







Administration and factory

www.cym.com.ar

Brig. Estanislao Lopez Nº 6 [S2108AIB] Soldini - Santa Fé - Argentina Tel: [54-341] 490 1100 | Fax: [54-341] 490 1366 E-mail: info@cym.com.ar

Metalcym Brasil

Rua Mário Junqueira da Silva nº 684 - Jd Eulina Campinas - SP - Brasil - CEP.13063-000 Tel: [55-19] 3242-9777 - Fax: [55-19] 3243-7236 E-mail: metalcym@metalcym.com.br www.metalcym.com.br